



## SAFETY DATA SHEET

According to: Regulation 453/2010 / EC of 20 May 2010 amending Regulation 1907/2006 / EC (REACH) as amended

### CP 390 PLASTIC PRIMER

Issue date: 2014-12-11

Revision date: 2015-06-01

Version: 6.3

Page 2 of 5

601-022-00-9	Xylene	215-535-7	1330-20-7	Flam. Liq. 3 H226 Acute Tox. 4 * H332 Acute Tox. 4 * H312 Skin Irrit. 2 H315	GHS02 GHS07 Wng H226, H312, H315, H332	40 – 50%	01- 2119488216- 32-XXXX
601-021-00-3	Toluene	203-625-9	108-88-3	Flam. Liq. 2 H225 Repr. 2 H361d *** Asp. Tox. 1 H304 STOT RE 2 * H373** Skin Irrit. 2 H315 STOT SE 3 H336	GHS02 GHS08 GHS07 Dgr H225, H361d (***) H304, H373 (**) H315, H336	40 – 50%	01- 2119471310- 51-XXXX

#### SECTION 4. FIRST AID MEASURES

##### 4.1 Description of first aid measures

General information:

See 11 point SDS

Inhalation:

Move to fresh air, ensure quiet and warmth, seek medical advice.

Eyes contact:

Do not close the eye, rinse with plenty of water (protect) healthy eye, remove contact lenses, seek medical advice.

Skin contact:

Immediately remove all contaminated clothing, wash with plenty of water with soap, seek medical advice.

Ingestion:

Wash out mouth thoroughly with water. Drink 2-4 glasses of water. Do not induce the vomiting.

##### 4.2 Most important symptoms and effects, both acute and delayed:

Seek medical advice.

##### 4.3 Indication of any immediate medical attention and special treatment needed:

Seek medical advice.

#### SECTION 5. FIREFIGHTING MEASURES

##### 5.1 Extinguishing media:

Suitable extinguishing media:

Water, vaporised water, foam, CO<sub>2</sub>.

Unsuitable extinguishing media:

Tight stream of water.

##### 5.2 Special hazards arising from the substance or mixture:

Under the influence of high temperature may produce CO, CO<sub>2</sub> vapours.

##### 5.3 Advice for firefighters:

Firemen have to wear self-contained breathing apparatus and protective clothing. Cool adjacent tanks by spraying water from a safe distance.

#### SECTION 6. ACCIDENTAL RELEASE MEASURES

##### 6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Remove ignition sources. Provide for sufficient ventilation. Avoid direct contact with releasing substance (vapours). Avoid contact with eyes and skin. Get acquainted with safety conditions (see point 7 and 8 SDS).

For emergency responders:

##### 6.2 Environmental precautions:

Keep away from drains, surface-water, ground-water and soil.

##### 6.3 Methods and material for containment cleaning up:

Poured substance should be absorbed with non-flammable materials : sand, silica, special granulated products. Keep to a minimum efflux area. Collect discards, store according to regulations (see point 13 SDS).

#### SECTION 7. HANDLING AND STORAGE

##### 7.1 Precautions for safe handling:

Keep away from heat; keep away from sources of ignition – do not smoke, do not eat, do not drink, do not breathe vapour, avoid contact with skin and eyes. Do not empty under pressure. Use only original tanks.

##### 7.2 Conditions for storage, including any incompatibilities:

Normal precautions taken when handling flammable substances. Store in hermetically closed containers In temp. 5-25°C. Place of storage should be dry. Protect from heat. Do not store near to sources of ignition.

##### 7.3 Specific end use(s):

Filler for plastic elements for car bodies.

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

##### 8.1 Control parameters

## SAFETY DATA SHEET

According to: Regulation 453/2010 / EC of 20 May 2010 amending Regulation 1907/2006 / EC (REACH) as amended

### CP 390 PLASTIC PRIMER

Issue date: 2014-12-11  
Revision date: 2015-06-01  
Limit values for Xylene

Version: 6.3

Page 3 of 5

Limit values for Toluene:

TLV: 100 ppm as TWA 150 ppm as STEL A4 (ACGIH 2001). BEI (ACGIH 2001).  
EU Limit Values: 50 ppm 221 mg/m<sup>3</sup> (8 hours)  
100 ppm 442 mg/m<sup>3</sup> (short-term) skin  
TLV: 50 ppm as TWA (skin) A4 BEI issued (ACGIH 2004).  
MAK: 50 ppm 190 mg/m<sup>3</sup>  
EU Limit Values: 50 ppm 192 mg/m<sup>3</sup> (8 hours)  
100 ppm 384 mg/m<sup>3</sup> (short-term) skin

#### 8.2 Exposure controls

Respiratory protection:

Gas mask with "A" type absorbing canister.

Hands protection:

Protective gloves for handling solvents (nitrile rubber).

Eyes protection:

Protective glasses.

Skin protection:

Suitable protective clothing.

Workplace:

Topical stays and exhausting ventilation.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

**Physical state:**

liquid

**Autoignition point:**

no data

**Colour:**

colourless, white transparent

**Vapour pressure:**

no data

**Odour:**

typical mixture of solvents

**Explosion limits:**

no data

**pH:**

no data

**Density:**

0,87 g/cm<sup>3</sup>

**Boiling point:**

> 110°C

**Water solubility:**

very poor

**Melting point:**

no data

**Octanol/Water partition coeff:**

no data

**Flash point:**

> 4°C

**Viscosity:**

10±2" DIN Cup 4 (ready for use)

### 9.2 Other information

**VOC**

no data

## SECTION 10. STABILITY AND REACTIVITY

10.1 Reactivity:

No data

10.2 Stability:

If handled according to the section 7 product is stable.

10.3 Possibility of hazardous reactions:

No data

10.4 Avoid contact with:

Strong acids and basis, oxidizers, high temperature, peroxides.

10.5 Materials to be avoided:

No data

10.6 Hazardous decomposition products:

Incomplete combustion will produce CO, CO<sub>2</sub> and toxic gases.

## SECTION 11. TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects:

There are no data on the toxicity of this product.

Toxicity for Xylene:

LD<sub>50</sub> (rat, oral) – 4300 mg/kg

LC<sub>50</sub> (rat, inhalation) – 22100 mg/m<sup>3</sup> (4 h)

LD<sub>50</sub> (rabbit, rat, skin) – no data

Toxicity for Toluene:

LD<sub>50</sub> (rat, oral) – 5000 mg/kg

LC<sub>50</sub> (rat, inhalation) – 15320 mg/m<sup>3</sup> (4 h)

Irritating effect:

Skin: prolonged or repeated exposure may result in drying of the epidermis, loss of the protective fat layer and permeation of the harmful substances to the subcutaneous layer.

Eyes: irritation of the mucosa and irreversible changes in the eye

Symptoms of poisoning:

Headaches, tiredness, muscle failure, partial or total loss of consciousness.

## SECTION 12. ECOLOGICAL INFORMATION

There are no data on the ecotoxicity of this product.



## SAFETY DATA SHEET

According to: Regulation 453/2010 / EC of 20 May 2010 amending Regulation 1907/2006 / EC (REACH) as amended

### CP 390 PLASTIC PRIMER

Issue date: 2014-12-11  
Revision date: 2015-06-01

Version: 6.3  
Page 4 of 5

12.1 Toxicity:  
Xylene acute toxicity for: (LC<sub>50</sub>/96 h) fish – 13500 - 17300 mg/l  
(LC<sub>50</sub>/48h) crustacea – 600 mg/l  
Toluene acute toxicity for: (LC<sub>50</sub>/96 h) fish - 13 mg/l  
(LC<sub>50</sub>/48h) crustacea – 11 mg/l  
12.3 Bioaccumulative potential: No data available  
12.4 Mobility in soil: No data available  
12.5 Results of PBT assessment: No data available  
12.6 Other adverse effects: No data available

The product is very poorly soluble in water. Do not allow to enter the sewage system, soil, or water reservoirs – inform the local authorities.

#### SECTION 13. DISPOSAL CONSIDERATIONS

##### 13.1 Waste treatment methods

Recommendation: Product must be disposed of by special means in accordance with local regulations.  
Remains of product: Remains of product in the tin should be carefully remove and leave to dry.  
Code of waste: 08 01 11\*  
Do not spill into drainage systems. Waste of this product must be burned in special installations for this purpose or dispose for authorized waste receiver.  
Clean tin: Tin carefully clean is not harmful waste.  
Code of waste : 15 01 04  
Spent packages dispose for authorized receiver who has adequate permission for waste management.  
Tin partly empty: See remains of products. Packs of an article containing residues of hazardous substances or contaminated by a hazardous waste code 15 01 10\*

#### SECTION 14. TRANSPORT INFORMATION

14.1 UN number: 1263  
14.2 UN proper shipping name: PAINT RELATED MATERIAL  
14.3 Transport hazard class(es): 3  
14.4 Packaging group: II  
14.5 Environmental hazards: No applicable  
14.6 Special precautions for user: Land transport: ADR/RID:  
Classification code: F1  
Tunnels: D1E  
Sea transport IMDG: EmS: F-E, S-E  
14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: No applicable

#### SECTION 15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislations specific for the ~~substance or~~ mixture  
67/548/EWG (2006/121/WE)  
91/155/EWG (2001/58/WE)  
1999/45/EC (2006/8/WE)  
1991/322/EWG  
2000/39/WE  
2006/15/WE  
2006/1907/WE (REACH)  
2004/42/WE  
2008/1272/WE (CLP)  
Other regulations: ADR (2007-2009), IMDG Code 2006 Edition.  
15.2 Chemical safety assessment – no chemical safety assessment has been carried out.

#### SECTION 16. OTHER INFORMATION

Full text of phrases from 3 point SDS according to CLP  
H225 Very flammable liquid and vapour  
H226 Flammable liquid and vapour  
H304 May be fatal if swallowed and enters airways  
H312 Harmful in contact with skin



## SAFETY DATA SHEET

According to: Regulation 453/2010 / EC of 20 May 2010 amending Regulation 1907/2006 / EC (REACH) as amended

### CP 390 PLASTIC PRIMER

Issue date: 2014-12-11  
Revision date: 2015-06-01  
H315 Causes skin irritation  
H332 Harmful if inhaled  
H336 May cause drowsiness or dizziness  
H361d Suspected of damaging the unborn child  
H373 May cause damage to organs through prolonged or repeated exposure  
H411 Toxic to aquatic life with long lasting effects  
EUH066 Repeated exposure may cause skin dryness or cracking  
Flam. Liq. 2 Flammable liquid category 2  
Flam. Liq. 3 Flammable liquid category 3  
STOT SE 3 Specific target organ toxicity – single exposure category 3  
Acute Tox. 4\* Acute toxicity category 4  
Skin Irrit. 2 Skin irritation category 2  
STOT RE 2 Specific target organ toxicity – repeated exposure category 2  
Repr. 2 Reproductive toxicity category 2  
Aquatic Chronic 2 Hazardous to the aquatic environment category 2  
Asp. Tox. 1 Aspiration hazard category 1

Version: 6.3

Page 5 of 5

The data contained in this Safety Data Sheet are based on our available knowledge at the last revision date. The data contained in this Safety Data Sheet give the conditions of safe use and storage of the product; this document does not give any guarantee as to the properties of the product.

Revision information: sections 2

All persons whose work is related to the mixture should receive a proper training in safety, hygiene and legal requirements related to a mixture in compliance with their responsibilities.